



PERFORMANCE

Model	Spring Color	Rated Load		Deflection at rated load		Isolator Weight †	
		lb	kN	in	mm	lb	kg
SHC-SN-15	White	15	0.07	1.0	25	0.6	0.3
SHC-SN-30	Yellow	30	0.13	1.0	25	0.6	0.3
SHC-SN-45	Orange	45	0.20	1.0	25	0.7	0.3
SHC-SN-60	Red	60	0.27	1.0	25	0.7	0.3
SHC-SN-100	Blue	100	0.44	1.0	25	0.7	0.3
SHC-SN-150	Black	150	0.67	1.0	25	0.7	0.3
SHC-SN-200	Grey	200	0.89	1.0	25	0.8	0.4

† weights are approximate

DIMENSIONS

Model	L	W	H
SHC-SN	in mm	in mm	in mm
15-200	2 1/2 64	2 51	6 152

NOTES

- Spring hanger with steel spring and welded steel housing
- Minimum 50% additional travel to solid
- Springs are powder coated, housings and compression cups are galvanized

Project:			1:	6:
Customer:			2:	7:
Consultant:			3:	8:
Dwg No.:	Rev:	Drawn by:	4:	9:
V-A Project Manager:			5:	10:
TAG:			QTY of sets required:	
COMMENTS:			EQUIPMENT:	
			DATE:	