VIBRO-ACOUSTICS®
A Swegon Group company

MEMBER VISCMA

tel: 416-291-7371 1-800-565-8401
fax: 416-291-8049 1-888-811-2264
web: www.vibro-acoustics.com
eml: info@vibro-acoustics.com

Rigid Restraint Kit (Standard Kit)

RRK-B

File No.: DS-RRK-B-001 Date: 20 Dec 2012
Supersedes: New Date: New

RRK-B-800 & -1400



RRB Rigid Restraint Bracket



RRK-B-800 RIGID RESTRAINT BRACKET KIT INCLUDES:
- (2) RRB-800 Brackets

RRK-B-1400 RIGID RESTRAINT BRACKET KIT INCLUDES:
- (2) RRB-1400 Brackets – Heavy Duty

PERFORMANCE FOR RRK KITS

RRK-B Kit Model	Max. Allowed Tension/Compression*		Bolt Size (Special Bolt)		Anchor Bolt Size Dia.		RRK Weight †	
	lb	N	**in**	mm	**in**	mm	**lb**	kg
RRK-B-800	**800**	3559	**1/2**	13	**1/2**	13	**2.2**	1.0
RRK-B-1400	**1400**	6229	**5/8**	16	**5/8**	16	**3.7**	1.7

† weights are approximate *maximum strut length to be 10 ft.

DIMENSIONS

RRB Bracket	L		W		H		d	
	in	mm	**in**	mm	**in**	mm	**in**	mm
RRB-800	**4**	102	**1 3/4**	44	**3**	76	**9/16**	14
RRB-1400	**4**	102	**1 3/4**	44	**3**	76	**11/16**	17

NOTES
- Restraint kits used to restrain non-structural components, e.g., equipment, ductwork, piping and conduit against seismic, wind, or blast forces.
- For attachment to concrete structure, please follow the specification of concrete anchor specifications on engineering calculation.
- Rigid brace (strut) should be secured to the bracket with both strut nut and hex nut.
- Strut by others
- For installation methods, please refer to installation instructions.
- Special grade bolts and nuts are required for attaching brackets to the strut. Please contact factory for details.

Project:			1:	6:
Customer:			2:	7:
Consultant:			3:	8:
Dwg No.:	Rev:	Drawn by:	4:	9:
V-A Project Manager:			5:	10:
			QTY of sets required:	
TAG:		EQUIPMENT:		
COMMENTS:				DATE: