

tel: 416-291-7371 1-800-565-8401
fax: 416-291-8049 1-888-811-2264

web: www.vibro-acoustics.com
eml: info@vibro-acoustics.com

File No.: DS-PSH3-002


Date: 07 Nov 2020

Supersedes: DS-PSH3-001

Date: 04 Oct 2016

PSH-3N

shown with cut-away



PERFORMANCE

Model	Spring Color	Rated Load		Deflection at rated load		Isolator Weight †	
		lb	kN	in	mm	lb	kg
PSH-3N-100	White	100	0.44	3.0	76	12.6	5.7
PSH-3N-200	Yellow	200	0.89	3.0	76	12.8	5.8
PSH-3N-400	Red	400	1.78	3.0	76	13.1	5.9
PSH-3N-700	Blue	700	3.11	3.0	76	13.6	6.2

† weights are approximate

DIMENSIONS: PSH-3N

Model	L		W		H		H2*		R	
PSH-3N	in	mm	in	mm	in	mm	in	mm	in	mm
100-700	5 1/2	140	5	127	12 1/2	318	5 7/8	149	3 1/2	89

* precompressed height

NOTES

- Spring hanger with steel spring and welded steel housing
- Springs are precompressed to 2/3 of deflection at rated load
- Hanger is designed to allow support rod misalignment through a 30-degree arc without contacting the hanger box
- Precompression plate serves as vertical uplift stopwasher for seismically restrained equipment, duct or piping. A second jam nut must be added to lock it in place
- Coupling (by others) is required for attaching to lower threaded rod
- Minimum 50% additional travel to solid
- All elements safe at solid loading
- All hardware zinc-plated or powder-coated
- Spring hanger boxes are galvanized or powder-coated

Project:			plan view of hanger locations <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		1:	6:
Customer:					2:	7:
Consultant:					3:	8:
Dwg No.:	Rev.:	Drawn by:			4:	9:
V-A Project Manager:					5:	10:
TAG:			QTY of sets required:			
COMMENTS:			EQUIPMENT:			
					DATE:	