



PERFORMANCE

Model	Spring Color	Rated Load		Deflection at rated load		Isolator Weight †	
		lb	kN	in	mm	lb	kg
SHB-SN-15	White	15	0.07	1.0	25	0.8	0.4
SHB-SN-30	Yellow	30	0.13	1.0	25	0.8	0.4
SHB-SN-45	Orange	45	0.20	1.0	25	0.9	0.4
SHB-SN-60	Red	60	0.27	1.0	25	0.9	0.4
SHB-SN-100	Blue	100	0.44	1.0	25	0.9	0.4
SHB-SN-150	Black	150	0.67	1.0	25	0.9	0.4
SHB-SN-200	Grey	200	0.90	1.0	25	1.0	0.5

† weights are approximate

DIMENSIONS

Model	L	W	H
SHB-SN	in mm	in mm	in mm
15-200	2 3/4 70	2 51	5 127

NOTES

- Spring hanger with steel spring in a welded steel housing
- Spring sits in a molded neoprene cup which includes a sleeve through the bottom hole
- Vertical uplift stopwasher must be added on spring hangers for seismically restrained equipment, duct or piping
- Minimum 50% additional travel to solid
- Springs are powder coated, housings and compression cups are galvanized

Project:			plan view of hanger locations 		1:	6:
Customer:					2:	7:
Consultant:					3:	8:
Dwg No.:					4:	9:
Rev:			5:		10:	
Drawn by:			QTY of sets required:			
V-A Project Manager:			EQUIPMENT:			
TAG:			DATE:			
COMMENTS:						