

2" (51 mm) Deflection SHRP Pre-Positioning Spring Hangers with Neoprene

SHRP-2SS

File No.: DS-SHRP-2SS-01


Date: September 2025

Supersedes:

Date:

SHRP 2SS

shown with cut-away



PERFORMANCE

Model	Spring Color outer-inner	Element Color	Rated Load		Deflection at rated load		Isolator Weight †	
			lb	kN	in	mm	lb	kg
SHRP-2SS-2100	Black-White	Black	2100	9.35	2.0	51	26.3	11.9
SHRP-2SS-2300	Black-Green	Black	2300	10.23	2.0	51	26.9	12.2
SHRP-2SS-2500	Black-Yellow	Black	2500	11.12	2.0	51	27.3	12.4
SHRP-2SS-3000	Black-Ivory	Black	3000	13.35	2.0	51	27.8	12.6
SHRP-2SS-3500	Black-Orange	Black	3500	15.57	2.0	51	28.0	12.7

† weights are approximate

DIMENSIONS: SHRP-2SS

Model	L		W		H	
	in	mm	in	mm	in	mm
2100-3500	6 3/4	171.5	5	127	17 1/2	444.5

NOTES

- Spring hanger with steel spring and neoprene element in series in a welded steel housing
- Vertical uplift stopwasher must be added on spring hangers for seismically restrained equipment, duct or piping
- 50% additional travel to solid
- Springs are powder coated. Hanger boxes are painted. Hardware is zinc plated.

Project:			plan view of hanger locations 		1:	6:
Customer:					2:	7:
Consultant:					3:	8:
Dwg No.:	Rev.:	Drawn by:			4:	9:
V-A Project Manager:					5:	10:
TAG:			EQUIPMENT:			
COMMENTS:			QTY of sets required:			
			DATE:			